

Spectra[®] Chain Link



Spectra[®] Color Chain Link... made to perform

Spectra[®] is the latest generation of Master Halco's residential, commercial and industrial chain link fence systems. It provides the corrosion protection of zinc, with the durability and attractive appearance of a colored polyester framework and extruded PVC fabric, to ensure years of attractive and reliable performance that blends in beautifully with the environment.

m m m



Our Spectra® Fencing System

Premium quality frame and fabric is guaranteed for 15 years.



Features and Benefits:

- Zinc-coated steel framework is thoroughly cleaned during the pre-treatment process, then color coated with a 3 mil minimum polyester layer for protection from corrosion.
- All galvanized wire has a 15 mil minimum extruded polyvinyl chloride coating for dual protection from corrosion and the elements.
- Fittings are made of galvanized steel with a 3 mil minimum of polymer layer for protection from corrosion.



1 ³/4″

1 ¹/₂"

1 1/4"

2″

Choose from 3 serene colors that blend in perfectly with the environment. Spectra[®] defines property lines, and will add value to any residential or commercial property.



Midnight Black Forest Green

Sierra Brown

Available Wire Gauges (Finish and Core) Use the finish gauge number when ordering.

6 gauge finish 9 gauge core



9 gauge finish 13 gauge core



5/8″

1/2″

3/8″



Spectra® Color Chain Link Recommendations

FABRIC		Type 2 Residential	Type 2 Commercial
Spectra® polyvinyl chloride extruded over zinc-coated steel core wire.	Fabric Gauge	9 gauge and 11 gauge finish	6 gauge, 8 gauge, and 9 gauge finish 6 gauge is not available for 3/8" mesh or 1/2" mesh
	Fabric Mesh	1-1/4", 1-1/2", 1-3/4", and 2"	3/8", 1/2", 5/8", 1", 1-1/4", 1-1/2", 1-3/4", and 2"
	Fabric Height	3', 42", 4', 5', and 6'	3', 42", 4', 5', 6', 7', 8', 9', 10', and 12'
	Fabric Selvage	Knuckle - Knuckle (KK) for 5' and Under. Knuckle - Knuckle (KK) or Knuckle - Twist (KT) for 6'.	Knuckle - Knuckle (KK) for 5' and under; for mesh sizes 1" and smaller. Knuckle - Knuckle (KK) or Knuckle - Twist (KT) for 6' and over.
FRAMEWORK - TYPE			
Spectra® polyester resin, 3 mils minimum, over galvanized steel ASTM F 1043, Group 1C, with a minimum yield strength of 50,000 PSI. Protective	Top Rail	1-3/8" O.D. Spectra® 17 Gauge or 16 Gauge	1-5/8" O.D. Spectra® Deluxe Quality (DQ) or Spectra® Full Weight Pipe
	Line Posts	1-5/8" O.D. Spectra® 17 Gauge or 16 Gauge	1-7/8" O.D. Spectra® Deluxe Quality (DQ) or Spectra® Full Weight Pipe
	- 36	AN ARRAY AND AN AND AND AND AND AND AND AND AND	2-3/8" O.D. Spectra® Deluxe Quality (DQ) or Spectra® Full Weight Pipe

50,000 PSI. Protective coating per ASTM 1043, external coating Type B, zinc with organic overcoat, 0.9 ounces per square foot minimum zinc coating with chromate conversion coating and verifiable polymer film.

Terminal Posts

1-7/8" O.D. Spectra® 16 Gauge

2-3/8" O.D. Spectra® 16 Gauge

2/16/24			
Gates			
Fabric	Same Gauge and Mesh as Chain Link Selected		
Frame	Same as Top Rail Selected		
Fittings			
Tension and Brace Bands	Polymer Coating, 3 Mils Minimum, Over Hot-Dipped Galvanized Pressed Steel		
Caps, Eye Tops, Rail Ends	Polymer Coating, 3 Mils Minimum, Over Hot-Dipped Galvanized Pressed Steel or Aluminum		
Sleeves	Polymer Coating, 3 Mils Minimum, Over Hot-Dipped Galvanized Steel		
Tie Wires	Polymer Coating, 3 Mils Minimum, Over Zinc-Coated Steel Wire		
Slats - Privacy			
Material Composition	Polyethylene Thermoplastic		
Colors	Green, Black, Brown, Gray, Redwood, Blue, Desert Sand		



Quality Products, Exceptional Service, Outstanding People

MasterHalco.com | 888-MH-Fence

Branch service centers are located throughout North America.



Available from:

2-3/8" O.D. Spectra® Deluxe Quality (DQ) or Spectra® Full Weight Pipe

2-7/8" O.D. Spectra® Deluxe Quality (DQ) or Spectra® Full Weight Pipe

4" O.D. Spectra® Deluxe Quality (DQ) or Spectra® Full Weight Pipe